2219P2
22" TFT MONITOR

SPECIFICATIONS

Panel	22'' (55.8 cm) TFT Active Matrix LCD, Super Narrow Bezel, Diagonal Hard Coating (3H), Anti-glare Treatment
Design Line	Professional Wide
Pixel / Dot Pitch	0.282 x 0.282 mm
Viewable Image Size (Diagonal)	
Display Area	473.76 x 296.10 mm
Brightness	300 cd/m^2
Contrast Ratio	10000:1 (DCR)
Typ. Response Time (tr)	2 ms
Viewing Angle	CR>10: 170 /160 Degrees
Compatibility	VESA,VGA,SVGA,XGA,SXGA,WXGA+,WSXGA+
Scanning Frequency	H:30~ 80kHz V:56~75 Hz
Pixel Frequency	165MHZ
Maximum Resolution	1680 x 1050@60Hz
Recommended Resolution	1680 x 1050@60Hz
Resolution Supported	640x480 @60Hz/72/75Hz, 800x600 @56Hz/60/72/75Hz, 848x480 @60Hz, 1024x768 @60/70/75Hz, 1280x768 @60/70/75Hz, 1280x960 @60Hz, 1280x1024 @60/75Hz, 1360x768 @60Hz, 1440x900 @60/75Hz, 1680x1050 @60Hz
Colours	16.7M
Signal Input	Analogue: D-Sub Digital: DVI-D
Connectors	Analogue: D-Sub Digital Input: DVI-D (TMDS)
Power Source	Power Input: Universal 110~240VAC, 50/60Hz
Power Consumption	On: <45W , standby: <1 W
Plug & Play	DDC 1/2B/CI or VESA DDC2B™
EPA ENERGY STAR ®	
User Control	Source(Auto)/Down,Eco/up, enu/Power,DCR/Right
Function	Brightness, Contrast, Eco Mode,Gamma(1,2,3),DCR,Focus, Clock, H/V Position, Color Temperature, Color Boost, Picture Boost, OSD Setup, AUTO Config, Reset,Information,Input select,DDC/CI EE
OSD Languages	2008 new 8 languages
Speaker	2 x 2 Watt
Emissions Standard	
Regulation	CUL, FCC, CE, TUV-bauart, TCO03, EPA, ISO 13406-2, Vista premium logo
Other Features	VESA 100mm Wall Mountable, Kensington Security Slot, -5-20° Tilt, 0~90° Pivot, 110mm Height Adjustment
Dimensions (WxHxD)	Monitor: 505.9 x 504.1 x 249.7 / Carton: 568 x 222 x 472
Weight	Net: 6.6 kg / Gross: 8.5 kg
Loading Qty w/pallet	40'' 880pcs 20'' 440pcs
Warranty	3 Years Parts & Labour
EAN Code	

Note: Specifications are subject to change without notice. *Wall mount arm & bracket not included.